

# Floodlighting

## Straight Outreaches

Straight outreaches are available to suit side entry luminaires with either 42mm or 60mm spigots, in widths from 0.5m up to 2.5m. For smaller sizes see our range of Side Entry Adaptors.

Straight outreaches have a tilt angle of 0° or 5°, and fit onto our standard Ø76mm column spigot. Maximum luminaire size and weight is 0.2m<sup>2</sup> and 20kg.

All Urban Lighting Group columns and brackets are made from hot dip galvanized steel, and can be painted or powder-coated in your choice of colours.

## Options and Accessories

- Powder-coat or 2 pack painted finish
- Custom design to suit your exact requirement



## Models - 42mm spigot

Model	Outreach	Tilt	Mounts
OR-42X500-S-0	500mm	0°	Single
OR-42X500-2X90-0	500mm	0°	2 @ 90°
OR-42X500-2X180-0	500mm	0°	2 @ 180°
OR-42X1000-S-0	1000mm	0°	Single
OR-42X1000-2X90-0	1000mm	0°	2 @ 90°
OR-42X1000-2X180-0	1000mm	0°	2 @ 180°
OR-42X1500-S-0	1500mm	0°	Single
OR-42X1500-2X180-0	1500mm	0°	2 @ 180°
OR-42X2000-S-0	2000mm	0°	Single
OR-42X2000-2X180-0	2000mm	0°	2 @ 180°
OR-42X2500-S-0	2500mm	0°	Single
OR-42X2500-2X180-0	2500mm	0°	2 @ 180°
OR-42X500-S-5	500mm	5°	Single
OR-42X500-2X90-5	500mm	5°	2 @ 90°
OR-42X500-2X180-5	500mm	5°	2 @ 180°
OR-42X1000-S-5	1000mm	5°	Single
OR-42X1000-2X90-5	1000mm	5°	2 @ 90°
OR-42X1000-2X180-5	1000mm	5°	2 @ 180°
OR-42X1500-S-5	1500mm	5°	Single
OR-42X1500-2X180-5	1500mm	5°	2 @ 180°
OR-42X2000-S-5	2000mm	5°	Single
OR-42X2000-2X180-5	2000mm	5°	2 @ 180°
OR-42X2500-S-5	2500mm	5°	Single
OR-42X2500-2X180-5	2500mm	5°	2 @ 180°

## Models - 60mm spigot

Model	Outreach	Tilt	Mounts
OR-60X500-S-0	500mm	0°	Single
OR-60X500-2X90-0	500mm	0°	2 @ 90°
OR-60X500-2X180-0	500mm	0°	2 @ 180°
OR-60X1000-S-0	1000mm	0°	Single
OR-60X1000-2X90-0	1000mm	0°	2 @ 90°
OR-60X1000-2X180-0	1000mm	0°	2 @ 180°
OR-60X1500-S-0	1500mm	0°	Single
OR-60X1500-2X180-0	1500mm	0°	2 @ 180°
OR-60X2000-S-0	2000mm	0°	Single
OR-60X2000-2X180-0	2000mm	0°	2 @ 180°
OR-60X2500-S-0	2500mm	0°	Single
OR-60X2500-2X180-0	2500mm	0°	2 @ 180°
OR-60X500-S-5	500mm	5°	Single
OR-60X500-2X90-5	500mm	5°	2 @ 90°
OR-60X500-2X180-5	500mm	5°	2 @ 180°
OR-60X1000-S-5	1000mm	5°	Single
OR-60X1000-2X90-5	1000mm	5°	2 @ 90°
OR-60X1000-2X180-5	1000mm	5°	2 @ 180°
OR-60X1500-S-5	1500mm	5°	Single
OR-60X1500-2X180-5	1500mm	5°	2 @ 180°
OR-60X2000-S-5	2000mm	5°	Single
OR-60X2000-2X180-5	2000mm	5°	2 @ 180°
OR-60X2500-S-5	2500mm	5°	Single
OR-60X2500-2X180-5	2500mm	5°	2 @ 180°