



Configurations			
Model Code	Outreach	Coating	Weight
70067	4.5m Single	Galvanized	336kg
70068	4.5m Single	Galvanized and Painted	336kg
70069	4.5m Double	Galvanized	376kg
70070	4.5m Double	Galvanized and Painted	376kg

Powercor / Citipower codes	
Code	Description
320322	V Category Decorative Column
354150	4.5m Single Outreach Bracket
354153	4.5m Double Outreach Bracket

Notes:

1. ULS moment and shear are calculated for wind loads per AS/NZS 1170.2 Region A, terrain category 2.
2. Serviceability deflection with 3.0kN top load is 247mm.
3. Designed and manufactured to:

AS 1798 Lighting poles and arms - Preferred dimensions
 AS/NZS 1170.2 Structural design actions - Part 2: Wind actions
 AS 4100 Steel structures
 AS 4680 Hot-dip galvanized (zinc) coatings

Powercor V Category Decorative Column 4.5m Single and Double Outreach		Luminaires allowed for: 2 x 0.20 sq.m 20kg nominal luminaires		 Urban Lighting Group <small>Innovative Streetscape Solutions</small>	
Dwg No. GA-10166	3-May-2021	ULS moment: 36.1 kNm	ULS shear: 5.4 kN	Urban Lighting Group Pty Ltd ABN 74 638 077 684 28 National Drive, Hallam Victoria 3803 T 1300 088 719 email: sales@urbanlightinggroup.com.au	
<small>CONFIDENTIAL: This drawing is the property of Urban Lighting Group Pty Ltd. No copies may be made without written permission</small>		Lift weight: kg	DO NOT SCALE	Sheet 1 of 1	A4