

Floodlighting

Mid-hinged Columns

Mid-hinged columns provide an ideal solution which allows maintenance to be carried out at ground level. This makes for a safer working environment especially where crane or work platform access is limited. These columns come standard with a base plate mount, a Ø76mm luminaire spigot, rope eyes and a padlock hasp for peace of mind.

All Urban Lighting Group columns and brackets are made from hot dip galvanized steel, and can be painted or powder-coated in your choice of colours.

Options and Accessories

- Luminaire brackets and adaptors
- Prefabricated foundation cages
- Foundation bolts and reinforcing cages
- Powder-coat or 2 pack painted finish
- Custom design to suit your exact requirement



Models

Model Code	Height	Mounting	Min. load weight	Max. load weight	Max. sail area ¹	Column weight
FL4XL1-MH	4.0m	4 M20 @ 233 PCD	6.0kg	18.0kg	0.6m ²	65kg
FL5XL1-MH	5.0m	4 M20 @ 233 PCD	6.0kg	18.0kg	0.6m ²	77kg
FL6XL1-MH	6.0m	4 M20 @ 233 PCD	6.0kg	18.0kg	0.6m ²	95kg
FL6L1-MH	6.0m	4 M20 @ 350 PCD	14.0kg	40.0kg	1.2m ²	132kg
FL8XL1-MH	8.0m	4 M20 @ 350 PCD	6.0kg	30.0kg	0.6m ²	145kg
FL8L1-MH	8.0m	4 M24 @ 350 PCD	26.0kg	80.0kg	1.2m ²	200kg
FL9L1-MH	9.0m	4 M24 @ 350 PCD	26.0kg	80.0kg	1.2m ²	224kg
FL10XL1-MH	10.0m	4 M20 @ 350 PCD	6.0kg	40.0kg	0.4m ²	204kg
FL12XL2-MH	12.0m	4 M24 @ 350 PCD	6.0kg	40.0kg	0.4m ²	245kg
FL15XL2-MH	15.0m	4 M30 @ 350 PCD	6.0kg	60.0kg	0.6m ²	389kg

1 Per AS/NZS 1170.2 region A terrain category 2