

Lighting Columns

Round Pipe 60mm Spigot Columns

Tapered round columns are ideal for many outdoor lighting projects. These columns are easy to install when combined with our foundation assemblies, and come standard with a base plate mount and a Ø60mm luminaire spigot.

All Urban Lighting Group columns and brackets are made from hot dip galvanized steel, and can be painted or powder-coated in your choice of colours.

Features

- Hot dip galvanized finish
- 60mm luminaire spigot
- M20 x Ø233mm base plate

Options and Accessories

- Powdercoated finish
- Standard or Coastal painted finish
- Prefabricated foundation cages
- Foundation bolts and reinforcing cages
- 76mm spigot
- Custom design

Models

Model Code	Height	Column Weight	Base plate	Spigot	Load ESA	Load Weight	ULS Moment ¹	ULS Shear
FL3P76X3-60	3.0m	27kg	4 M20 @ 233	60mm	0.25m ²	25kg	1.23kNm	0.53kN
FL3.5P76X3-60	3.5m	31kg	4 M20 @ 233	60mm	0.25m ²	25kg	1.51kNm	0.57kN
FL4P76X3-60	4.0m	32kg	4 M20 @ 233	60mm	0.25m ²	25kg	1.83kNm	0.62kN
FL4.5P76X3-60	4.5m	37kg	4 M20 @ 233	60mm	0.25m ²	25kg	2.16kNm	0.66kN
FL5P76X3-60	5.0m	40kg	4 M20 @ 233	60mm	0.25m ²	25kg	2.55kNm	0.71kN
FL5.5P76X3-60	5.5m	43kg	4 M20 @ 233	60mm	0.25m ²	25kg	2.98kNm	0.76kN
FL6P76X4-60	6.0m	50kg	4 M20 @ 233	60mm	0.25m ²	25kg	3.46kNm	0.82kN
FL6.5P76X5-60	6.5m	63kg	4 M20 @ 233	60mm	0.25m ²	25kg	3.96kNm	0.87kN
FL7P89X4-60	7.0m	70kg	4 M20 @ 233	60mm	0.25m ²	25kg	4.85kNm	1.03kN
FL7.5P89X5-60	7.5m	89kg	4 M20 @ 233	60mm	0.25m ²	25kg	5.50kNm	1.10kN
FL8P89X5-60	8.0m	95kg	4 M20 @ 233	60mm	0.25m ²	25kg	6.22kNm	1.16kN

1

Base moment and shear are calculated for AS/NZS 1170.2 Region A Terrain 2

